

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049302 A1

(51) International Patent Classification⁷: **B29C 47/08**,
B29D 23/00

(21) International Application Number:
PCT/CA2004/002016

(22) International Filing Date:
24 November 2004 (24.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,450,560 24 November 2003 (24.11.2003) CA

(71) Applicants and

(72) Inventors: LUPKE, Manfred, A., A. [CA/CA]; 92 Elgin
Street, Thornhill, Ontario L3T 1W6 (CA). LUPKE, Ste-
fan, A. [CA/CA]; 32 Vintage Lane, Thornhill, Ontario L3T
1X6 (CA).

(74) Agents: HALL, Warren, S. et al.; Dennison Associates,
133 Richmond Street West, suite 301, Toronto, Ontario
M5H 2L7 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PIPE MOLDING SYSTEM WITH VACUUM AND TEMPERATURE CONTROLS OF COOLING PLUGS



(57) Abstract: A pipe mold produces plastic pipe with an internal wall having a first wall portion and a second wall portion. The pipe mold includes a two stage cooling plug to assist in setting the pipe wall. The first cooling stage is controlled to remove heat from the pipe wall to partially set the plastic without excessive cooling. The partially set plastic pipe then passes over a second stage where less precision in the cooling of the pipe occurs. The partially set plastic is more tolerant and subject to less damage. Preferably both the first and second stages include separate temperature sensors and control arrangements for varying the cooling medium of each stage. In a preferred embodiment a cooling medium is circulated through a first stage at a temperature and at a flow rate to maintain the first stage within a narrow temperature range about the temperature of the cooling medium. The staged cooling plug allows better control at initial startups and with varying operating conditions.